



Assembly Instructions


Components:




Debut Base



Corner Cap
(Orange / Charcoal)



Linkers
(Opaque)



Top Spacer
(Opaque)

Before you begin take time to familiarise yourself with the components.

1. Arrange the Bases into your chosen configuration, leaving a 5cm gap between each Base frame. Hook on any Steps.



2. Pop off the Corner Caps on any Debut Bases that are to received a Guardrail.



Guardrails are not inserted into the cavity at this stage.

3. Once you are happy with the layout and position of the stage, begin to link the Bases together using the appropriate sized Linkers. Where two corners meet use a Duo Linker, where three corners meet secure with a Trio Linker and so on.
(See table & diagram)

Which Linker should I use?

Number of Corners

2	Duo Linker Trio Linker Quartet Linker
3	
4	



4. The Base Linkers simply slip over any Corner Caps. If the Corner Cap has been popped, Linkers or Spacers should be placed directly onto the Base frame.



5. Use the Top Spacers on any single corners to ensure the Safe-Grip Tops sit evenly.

6. Drop the Safe-Grip Tops into place starting in one corner and working outwards, taking care to manoeuvre between the Base frames.



7. Insert the Guardrails or Chair Stop Rails into the cavities within the Bases.



Your stage is now ready.

Using Your Storage Truck

To ensure a sturdy base before loading, secure the brakes on the Truck casters. Begin by lowering the Safe-Grip Tops onto the four uprights of the Truck. The Debut Bases should be stacked directly on top of the stack of Safe-Grip Tops. Turn each Base slightly to form a spiral.



Each Truck will take up to 28 Safe-Grip Tops & Bases.

Caring for your Topdeck Debut

To keep your Debut looking pristine, wash with warm water and a mild detergent. Dry with a soft cloth immediately.

